

FICHA TECNICA

PRODUCT: NAC14921-xx

FECHA DE ACTUALIZACIÓN: 12/12/2023

*La presente actualización anula a la anterior.

DESCRIPTION: CLEAR ACRYLIC TOP COAT

CHARACTERISTICS: CLEAR ACRYLIC TOP COAT, GOOD SURFACE RESISTANCES. CAN BE USED AS A SELF SEALER. SUITABLE FOR OUTDOOR USE IF USED WITH NC119 AT 20%. IT CAN BE USED AS A CLEAR BASE FOR PIGMENTED TOP COATS.

FIELD OF APPLICATION: ALL KIND OF FURNITURE, DOORS, KITCHEN DOORS.

TECHINCAL DATA:

| | | | |
|----------------------|------------|--|--|
| VISCOSITY AT (DIN 4) | 42'' |  <p style="text-align: center;">APLICACION</p> | <p>Cantidad: 120 g/m² Mezclar y aplicar como se describe en ''Preparación del producto''</p> |
| VISCOSITY A (DIN 8) | --- | | |
| DENSITY | 0.93 ±0.05 | | |
| FLASH POINT | 20°C | | |
| SOLID CONTENT | 27.0% ±0.2 | | |
| SHELF LIFE | 24 MESES | | |
| GLOSS | 0.5° | | |
| FINESS | ≤15μ | | |

PRODUCT PREPARATION:

| | CODE | SPRAY GUN | | ROBOT | | CURTAIN | | ROLLER | |
|----------------|------------|------------------|--------|--------|--------|---------|--------|--------|--------|
| | | WEIGHT | VOLUME | WEIGHT | VOLUME | WEIGHT | VOLUME | WEIGHT | VOLUME |
| HARDENER | NC119 | 100:10 | 10% | | | | | | |
| ALTERNATIVE | NC940 | 100:20 | 20% | | | | | | |
| ACCELERANT | | | | | | | | | |
| PHOTOINITIATOR | | | | | | | | | |
| SOLVENT | ND5920 | | 20-30% | | | | | | |
| ALTERNATIVE | NF4028 | | 20-30% | | | | | | |
| POT-LIFE | +6H | | | | | | | | |
| VISCOSITY A+B | 38''(DIN4) | 20% ND5920= 18'' | | | | | | | |



- DRYING TIMES:
- DUST-FREE DRY: 15 min.
- DRY TO THE TOUCH: 40 min.
- READY FOR SANDING: 4-6 hours
- ALWAYS MIX BEFORE USE
- PRODUCT FOR PROFESSIONAL AND INDUSTRIAL USAGE ONLY.
- DO NOT WORK WITH THESE PRODUCTS AT TEMPERATURES LOWER THAN 15°C
- PRODUCT MAY CAUSE MILD YELLOWING. FOR NON YELLOWING PRODUCTS USE OUR ACRYLIC SEALERS.
- DISCLAIMER: WE DO NOT TAKE RESPONSIBILITY IF THE END RESULT IS AFFECTED BY FACTORS BEYOND OUR CONTROL.

